

YORK S3

KU061D

CE UNI EN ISO 20345:2012 S3 SRC

Low safety shoe, back WRU leather thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic and antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

THIS PRODUCT COMPLIES WITH THE REQUIREMENTS OF THE STANDARD ASTM F2413-18:

- Impact resistant footwear (I)
- Compression resistant footwear (C)
- Puncture Resistant Footwear (PR)

Size 35-49 Shoe weight Sz 42 gr. 500




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 COMPONENTS AND AUTOMOTIVE  WOOD METAL CARPENTRY 
LOGISTICS AND LIGHT INDUSTRY

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an **excellent anti-slipping product**.

This sole is called **Kube**, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole.

With thanks to these special characteristics Kube obtained the maximum certification against slipping: **jobs on inclined roofs** (UNI 11583:2015).

**ANTISLIPPING
TEST RESULTS**

request results

SRAceramic +
NaLSHEEL \geq = 0,28

0,37

FLAT \geq = 0,32

0,39

SRBsteel +
glycerolHEEL \geq = 0,13

0,20

FLAT \geq = 0,18

0,30



SRA+SRB=

SRC

ANTI-SLIPPING SOLE