

Ref. **9GAL130**

Indoor and dry environments

Low

Low shoes



**HRO**



The +

Lightweight (430 g in size 42)  
Flexible and cushioning  
Breathable

### PURCHASE PACKAGING

| Ref.       | Size | Carton |
|------------|------|--------|
| 9GAL130037 | 37   | 6      |
| 9GAL130038 | 38   | 6      |
| 9GAL130039 | 39   | 6      |
| 9GAL130040 | 40   | 6      |
| 9GAL130041 | 41   | 6      |
| 9GAL130042 | 42   | 6      |
| 9GAL130043 | 43   | 6      |
| 9GAL130044 | 44   | 6      |
| 9GAL130045 | 45   | 6      |
| 9GAL130046 | 46   | 6      |
| 9GAL130047 | 47   | 6      |

*Some sizes may only be available in certain countries*

*See also*

### VARIANTS



9GAL120

### DESCRIPTION

The GALAXITE ESD HRO sneaker is very lightweight, flexible and breathable: at the forefront of comfort.

Its EVA/rubber outsole offers excellent cushioning, durability and grip.

GALAXITE is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

|                         |                |                        |                           |
|-------------------------|----------------|------------------------|---------------------------|
| Color                   | Black          | Insole                 | Removable, perforated EVA |
| Color 2                 | Red            | Reinforcement material | TPU                       |
| Weight                  | 430 g          | Reinforcement location | Front                     |
| Upper                   | Mesh           | Closing                | Lacing closure            |
| Toecap                  | Composite      | Lining                 | Breathable 3D mesh        |
| Puncture resistant sole | Textile        |                        |                           |
| Midsole                 | EVA            |                        |                           |
| Outsole                 | Rubber nitrile |                        |                           |

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0808

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.