

Ref. 9GOLD60

Specialties

Low

Low shoes



The +

- *Breathability
- *Front and back reinforcements
- *PU/PU outsole: impact cushioning. Protects the back and joints
- *Fashion style

PURCHASE PACKAGING

Ref.	Size	Carton
9GOLD60035	35	6
9GOLD60036	36	6
9GOLD60037	37	6
9GOLD60038	38	6
9GOLD60039	39	6
9GOLD60040	40	6
9GOLD60041	41	6

Some sizes may only be available in certain countries

DESCRIPTION

GOLD is a low safety shoe inspired by fashion design with mesh upper and lining which offer high breathability and comfort.

Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.

GOLD is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility.

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Gold	Main assembly	Injected
Weight	441 g	Closing	Lacing closure
Upper	Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/11/20/2750

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.