

OROSHI S1P

3R172T

CE UNI EN ISO 20345:2012 S1P SRC

Low safety shoe, perspiring and abrasion resistant technical fabric with silkscreen printing and MICROWASH thickness 1,8-2,0 mm. Highly perspiring and abrasion resistant fabric lining. Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE 3RUN three densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC ANTITORSION** insert in the sole to assure stability on uneven ground

INSOLE MEMORY, three-materials extracomfort with soft latex Memory no-stress in the heel zone resistant to the body pressure. Perspiring, removable, anatomic, absorbing, antistatic and anti-bacterial

Size 36-47 Shoe weight Sz 42 gr. 470



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 COMPONENTS AND AUTOMOTIVE  WOOD METAL CARPENTRY 
LOGISTICS AND LIGHT INDUSTRY

SOLE



3Run is a line with a **sporty** and youthful character, developed for those who work **indoors** and **outdoors on regular surfaces**. 3Run belongs to the **3D generation**. This shoe therefore has **3 different PU injected layers** with relative densities, each specialized to maximize comfort, anti-slip and foot stability. Some of these models are also equipped with an **antitorsion** insert to guarantee further support to the foot at every step.

ANTISLIPPING TEST RESULTS



SRC
ANTI-SLIPPING SOLE

SRA ceramic + NaLS	HEEL >= 0,28 FLAT >= 0,32	0,47 0,47
SRB steel + glycerol	HEEL >= 0,13 FLAT >= 0,18	0,23 0,26

PLUS

**ANTI TORSION**

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the central part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.

**3D TRIPLA DENSITA' INIETTATA**

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.

**MICROWASH**

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

**MEMORY FOAM INSOLE**

The MEMORY FOAM insole guarantees an excellent comfort thanks to the innovative material of which it is made, which allows it to adapt to the shape of the foot. This, in addition to making walking more pleasant, supports posture, improves the fit of the shoe and distributes the body weight better. Moreover, this stabilizes the foot and reduces the impact with the ground, absorbing shocks and guaranteeing an excellent shock absorber.