

LIPARI S1PL FO SR

3H182NG

EN ISO 20345:2022+A1:2024 S2 FO SR ESD

LOW SAFETY SHOE

35-49

3HYBRID Cushioning

Low holed shoe, MICRO-tech technical fabric thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Soft and lined tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN 22568

PL MIDSOLE flexible antiperforation composite fabric according to EN 22568

SOLE 3HYBRID three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping

ANTI TORSION insert in the sole to assure stability on uneven ground

MEMORY INSOLE three-materials extra comfort insole, with soft latex Memory cushion, ensuring no stress in heel zone and resistant to body pressure.

Perspiring, removable, anatomic, absorbing, antistatic and anti-bacterial and ESD.

Footwear meets the requirement in accordance with IEC 61340-5-1:2024 (IEC 61340-4-3:2017) for electrical resistance ESD.

FO sole resistant to hydrocarbons

SR antislipping resistance


Size 35-49 Shoe weight Sz 42 gr. 485

AREAS OF APPLICATION

 Logistics and Light Industry

 Automotive Components

 Construction and Building Sites

 Metal and Wood Carpentry


CERTIFICATIONS APPLIED



PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)



Antistatic Footwear



Hydrocarbon Resistance



DGUV 112-191



Heel Energy Absorption

TECHNOLOGIES AND MATERIALS



No metal



ESD - Electrostatic Discharge




Metal-Free



High Visibility



High Breathability




Mondo Point 11



Extreme Lightness



Slip Resistance (optional glycerin test)



Microtech



Three to be™ - Triple Density Injection



Anti-Torsion Sole

ANTI-SLIP RESULTS

*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31	≥ 0.47		≥ 0.19	≥ 0.23



Three to be™ - Triple Density Injection

Three to Be® - Tripla Densità Iniettata technology represents one of the most advanced results of our R&D efforts. Patented by Giasco, it integrates three entirely polyurethane-injected sole layers to optimize safety shoe performance in terms of comfort, stability, and slip resistance.



Anti-Torsion Sole

The Anti Torsion system uses a thermoplastic shank designed to increase stability on irregular and wet surfaces. Unlike standard shanks, it flexes with the foot's natural motion, reducing the risk of twists and falls. Ideal for outdoor work, especially in construction, where surface control is critical.

3HYBRID Cushioning

3Hybrid is a line that, thanks to the sole design, ensures maximum shock absorption and energy return throughout the entire lifespan of the safety footwear. These high cushioning properties are provided on one hand by the special low-density, ultra-soft compounds and on the other by a three-dimensional lateral design that maximizes the sole's elasticity. Also on the side of the work shoe, there is a spoiler designed to provide greater foot stability and firmness, thus maximizing protection. Lastly, this safety shoe features a tread with a specific lug pattern designed to offer excellent slip resistance for indoor and light outdoor environments.

