





DANCE S1P

KU055HF

CE UNI EN ISO 20345:2012 S1P SRC ESD

Low safety shoe, suede back leather thickness 1,8 - 2,0 mm External 3D fabric, perspiring and abrasion resistant. Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN

MIDSOLE flexible antiperforation composite fabric according

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping SRC

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 35-42 Shoe weight Sz 42 gr. 485



CERTIFICATIONS









TECHNOLOGIES AND MATERIALS















SECTORS

COMPONENTS AND AUTOMOTIVE

% WOOD METAL CARPENTRY



LOGISTICS AND LIGHT INDUSTRY & ESD AREAS

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product.

This sole is called **Kube**, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole.

With thanks to these special characteristics Kube obtained the maximum certification against slipping: **jobs on inclined roofs** (UNI 11583:2015).

TEST RESULTS	request	results
SRA		
ceramic +	HEEL $\geq = 0.28$	0,37
NaLS	FLAT ≥ = 0,32	0,39
SRB		
steel +	HEEL \geq = 0,13	0,20
glycerol	FLAT ≥ = 0,18	0,30
SRA+SRB= SRC		

PLUS



AIRNET®
Airnet® is a certified technology that guarantees the maximum perspiration of the foot by wearing a strong and abrasion resistant safety shoe. Thanks to its construction air tunnel, facilitates the air passage and the material, 100% polyester, guarantees a perfect resistance to abrasion, to traction, to tearing and to washing.