

Ref. **9ORTL**

Specialties

Low

Low shoes



S2

0%
METAL

SR

FO



The +

- * Easy-on and easy-off.
- * Protective cover.
- * Rounded heel for more comfortable driving.

PURCHASE PACKAGING

Ref.	Size	Carton
9ORTL35	35	10
9ORTL36	36	10
9ORTL37	37	10
9ORTL38	38	10
9ORTL39	39	10
9ORTL40	40	10
9ORTL41	41	10
9ORTL42	42	10
9ORTL43	43	10
9ORTL44	44	10
9ORTL45	45	10
9ORTL46	46	10
9ORTL47	47	10

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
 External sole in double density PU/PU
 Upper: breathable Microfiber in PU
 Breathable mesh lining

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Color 2	Grey	Closing	Scratch closure
Weight	406 g	Lining	Breathable 3D mesh
Upper	Microfiber		
Toecap	Composite		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/23/0975 EXT 01/06/23

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S2

Safety shoes

S2 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Water penetration and absorption resistant upper

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance