

# SANTA FE S1P

71T83C

CE UNI EN ISO 20345:2012 S1P SRC ESD CLASS 3

Low holed shoe, suede back leather thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Soft, lined and padded tongue.

**COMPLETELY METAL FREE SHOE**

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ERGO SAFE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**


**INSOLE 5000 three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial.

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance **ESD class 3 (electric dissipative footwear)**

**Size 36-47 Shoe weight Sz 42 gr. 490**



## MATERIALS



## TECHNOLOGIES



## SECTORS



## SOLE



**Ergo Safe** is the safety shoe useful for people who have problems with **back and joint pains**. It is in fact the only **ergonomic** shoe in the market, studied to give a solution to these needs and in the same time to assure a complete protection.

This is possible thanks to the round sole, that allows a uniform discharge of body weight all

along the sole of the foot, giving a good feeling to the back, the knees and to the heels.

Ergo is also studied to improve walking, by giving a better **blood circulation** and a saving of energy at the end of the day.

## ANTISLIPPING TEST RESULTS



<b>SRA</b> ceramic + NaLS	<b>HEEL</b> >= 0,28 <b>FLAT</b> >= 0,32	<b>0,31</b> <b>0,35</b>
<b>SRB</b> steel + glycerol	<b>HEEL</b> >= 0,13 <b>FLAT</b> >= 0,18	<b>0,22</b> <b>0,22</b>