



NORM SPECIFICATION

EN ISO 20345:2022 (S3S HRO FO SR)

Personal protective equipment - Safety footwear

DESCRIPTION

• modern safety low shoes with a composite antipuncture midsole and a composite toe cap, which protects against compression with a force of up to 15 kN or a load weighing up to 20 kg from a height of 1 m • antistatic outsole made of a combination of polyurethane and very durable rubber is not only safety thanks to the anti-slip properties but also resistant to oils and abrasion • the upper part is made of genuine leather "NUBUCK", and the inner lining is made of breathable polyester • reflective elements guarantee increased user visibility • this model is equipped with a comfortable inner insole, which thanks to the gel heel absorbs shocks even better and brings a maximum feeling of comfort during work • these shoes look like sports shoes, but they perfectly protect your feet • extra pair of shoelaces in each box



PRODUCT CODE - 02010577 XX YYY

Colours - XX

60 - black, light green

Sizes - YYY

037 - 37	038 - 38
039 - 39	040 - 40
041 - 41	042 - 42
043 - 43	044 - 44
045 - 45	046 - 46
047 - 47	048 - 48

COLOUR VARIANTS



60 - black, light green

MATERIALS

Antipuncture midsole material: composite
Upper material: nubuck leather
Toe cap material: composite
Outsole material: PU/rubber
Lining material: polyester mesh

FEATURES

Item weight: 660 g
Industry: Construction, Mining and quarrying, Heavy industry
Features: Energy absorption in heel area - E, Metal free - MF, Antislip outsole - SR, Protection against water penetration and absorption - WPA, Breathable upper, Fuel and oil resistant outsole - FO, Antistatic shoes - A, Antiperforation non-metallic midsole - PL, PS, Non-metallic safety toe cap - S

PACKAGING

Packaging type	Pieces in packaging	Size	Volume	Weight
CTN	10 PR	35 x 42 x 65 cm	95.55 dm³	17.5 kg
Pair	1 PR		9555 cm³	1.75 kg

SIZE
TABLES

Scan or Tap

