

Ref. **9FLEL1R**

Multipurpose

Low

Low shoes



The +

- *RCS Label = upper made of recycled materials
- *Soft PU/PU outsole: cushioning and comfort.
- *Frontal overprotection: durability.
- *Wide cleats and flex lines: optimized adaptability to the ground.
- *Polyester upper mesh: excellent breathability (laboratory tested).

PURCHASE PACKAGING

Ref.	Size	Carton
9FLEL1R035	35	6
9FLEL1R036	36	6
9FLEL1R037	37	6
9FLEL1R038	38	6
9FLEL1R039	39	6
9FLEL1R040	40	6
9FLEL1R041	41	6
9FLEL1R042	42	6
9FLEL1R043	43	6
9FLEL1R044	44	6
9FLEL1R045	45	6
9FLEL1R046	46	6
9FLEL1R047	47	6
9FLEL1R048	48	6

Some sizes may only be available in certain countries

DESCRIPTION

CLAW FLEX is a lightweight, flexible and breathable safety sneaker. Made of 30% of recycled material (complete upper, lining, insole, laces), it has the RCS label.

With a recycled polyester upper and skinny TPU reinforcement on the front, CLAW FLEX ensures optimal breathability and durability in dry environments.

Its low density PU/PU outsole guarantees all day comfort.

Its aluminum / composite protection system contributes to its sporty look.

SECTORS

Light Industries

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Insole	PU Foam, removable, with shock absorber
Color 2	Green	Reinforcement location	Front
Weight	578 g	Lining	Breathable 3D mesh
Upper	Polyester mesh		
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/24/1817

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

COVERPERF - Breathability



Shoes tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 4g/h.

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S1PS

Safety shoes

S1PS Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance