

Ref. **9AGH010**

Multipurpose

High

High shoes



S3

SR

FO



The +

- * Value for money
- * Full grain leather upper
- * Reflective stripe with multiple faces
- * PU2D injected outsole
- * Defined and raised heel

PURCHASE PACKAGING

| Ref. | Size | Carton |
|------------|------|--------|
| 9AGH010034 | 34 | 10 |
| 9AGH010035 | 35 | 10 |
| 9AGH010036 | 36 | 10 |
| 9AGH010037 | 37 | 10 |
| 9AGH010038 | 38 | 10 |
| 9AGH010039 | 39 | 10 |
| 9AGH010040 | 40 | 10 |
| 9AGH010041 | 41 | 10 |
| 9AGH010042 | 42 | 10 |
| 9AGH010043 | 43 | 10 |
| 9AGH010044 | 44 | 10 |
| 9AGH010045 | 45 | 10 |
| 9AGH010046 | 46 | 10 |
| 9AGH010047 | 47 | 10 |
| 9AGH010048 | 48 | 10 |
| 9AGH010049 | 49 | 10 |

Some sizes may only be available in certain countries

See also

DESCRIPTION

AGATE II is an ankle safety shoe. Its full grain upper brings a better resistance and breathability than split leather whereas the ankle padding provides supports to the wearer. The polyester mesh lining improves breathability and hence comfort. The out & mid-soles are made of injected polyurethane of different density which balance comfort and durability. This shoe features a steel toe-cap and plate for protection against puncture and fall of heavy objects. The retro-reflective band with patterns improves safety of wearers while in dark environments. AGATE II is equipped with a cleated outsole with good adhesion properties. Ideal for indoor as well as outdoor works.

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
Delivery driver, ...

VARIANTS



9AGL010

TECHNICAL FEATURES

| | | | |
|-------------------------|-----------------------------|---------------|-------------------------------------|
| Color | Black | Main assembly | Injected |
| Weight | 622 g | Closing | Lacing closure |
| Upper | Full grain leather | Lining | Moisture wicking non-woven membrane |
| Toecap | Steel | Defined heel | |
| Puncture resistant sole | Steel | | |
| Midsole | PU | | |
| Outsole | PU | | |
| Insole | Removable, textile and foam | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/23/0869

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance