

# CAMBRIDGE S3

AC068D

CE UNI EN ISO 20345:2012 S3 SRC

High safety shoe, WRU back leather thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.  
Shoe with refracting fabric insert.  
Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic and antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

**Size 36-51 Shoe weight Tg 42 gr. 615**








## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS

 FARMING AND MINING  COMPONENTS AND AUTOMOTIVE   
WOOD METAL CARPENTRY  BUILDING AND HEAVY INDUSTRY   
LOGISTICS AND LIGHT INDUSTRY

## SOLE



**Action** is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## ANTISLIPPING TEST RESULTS

**SRC**

ANTI-SLIPPING SOLE

<b>SRA</b>		
ceramic +	<b>HEEL &gt;= 0,28</b>	<b>0,39</b>
NaLS	<b>FLAT &gt;= 0,32</b>	<b>0,36</b>

<b>SRB</b>		
steel +	<b>HEEL &gt;= 0,13</b>	<b>0,26</b>
glycerol	<b>FLAT &gt;= 0,18</b>	<b>0,22</b>