

Ref. **9FLH370**

Outdoor

High

High shoes



S3



The +

- *Shaped cleats: adherence and gripping on rough floors.
- *Grooves for liquid and mud dispersement.
- *Raised heel 1 cm and lateral edges: reinforced grip on ladders.
- *Front TPU reinforcement.

PURCHASE PACKAGING

Ref.	Size	Carton
9FLH370037	37	6
9FLH370038	38	6
9FLH370039	39	6
9FLH370040	40	6
9FLH370041	41	6
9FLH370042	42	6
9FLH370043	43	6
9FLH370044	44	6
9FLH370045	45	6
9FLH370046	46	6
9FLH370047	47	6
9FLH370048	48	6
9FLH370049	49	6

Some sizes may only be available in certain countries

See also

VARIANTS



9FLL370

DESCRIPTION

FLINT is a formidable efficiency safety shoe. Specially designed for construction industry, FLINT benefits from a PU / PU sole resistant to abrasion, oils and hydrocarbons and equipped with prominent grips. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. FLINT features a toe-cap and an anti-penetration plate made of steel for optimal protection.

SECTORS

Mining

Extracting Oil and Gas

Energy (production and distribution)

Infrastructure, building industry

TECHNICAL FEATURES

Color	Caramel	Main assembly	Injected
Weight	701 g	Closing	Lacing closure
Upper	Action leather	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/04/21/0797

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol