

Ref. **9ROCK10**

Outdoor

High

High shoes



The +

- *Shaped cleats: adherence and gripping on rough floors.
- *Grooves for liquid and mud dispersement.
- *Raised heel 1 cm and lateral edges: reinforced grip on ladders.
- * Waterproof membrane: impermeability.
- *PU reinforcement piece: ankle support.
- *EVA perforated insole with silicone insert: comfort and breathability.

DESCRIPTION

ROCKET is the ideal protection for construction. This shoe has a PU / nitrile rubber outsole resistant to abrasion, oils and hydrocarbons and equipped with prominent grips. Its breathable insole (textile and EVA with perforations) incorporates a gel insert to relieve pressure points under the foot. Its full grain water-repellent leather upper has an anti-twist ankle reinforcement. ROCKET features a toe-cap and an anti-penetration plate made of composite for optimal protection.

SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

PURCHASE PACKAGING

Ref.	Size	Carton
9ROCK10035	35	6
9ROCK10036	36	6
9ROCK10037	37	6
9ROCK10038	38	6
9ROCK10039	39	6
9ROCK10040	40	6
9ROCK10041	41	6
9ROCK10042	42	6
9ROCK10043	43	6
9ROCK10044	44	6
9ROCK10045	45	6
9ROCK10046	46	6
9ROCK10047	47	6
9ROCK10048	48	6

Some sizes may only be available in certain countries

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA with silicone piece
Weight	745 g	Main assembly	Cemented
Upper	Full grain leather	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/04/21/2140

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

WR

Water repellent shoe

HRO

Heat contact resistant outsole (60 seconds at 300°C)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.