

SOFTBALL S3L FO SR

KU037T

CE EN ISO 20345:2022 S3L FO SR ESD

ANKLE SAFETY SHOE

39-47

KUBE Supergrip

High safety shoe, suede back WPA leather thickness 1,8-2,0 mm. Highly perspiring and abrasion resistant fabric lining. Shoe with refracting fabric insert. Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015** (test report. 4312114 E)

TOECAP 200J polymeric composite non-thermic according to EN 22568

PL MIDSOLE flexible antiperforation composite fabric according to EN 22568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO

5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping

INSOLE 5000 three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

FO sole resistance to hydrocarbons

SR slip resistance

Size 39-47 **Shoe weight Sz 42 gr. 600**

↪ AREAS OF APPLICATION



Sloped Roofs



Logistics and Light Industry



Automotive Components



Metal and Wood Carpentry



ESD Area



↪ CERTIFICATIONS APPLIED



Water Penetration and Absorption (WPA)



PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)



Slip Resistance (mandatory ceramic-Nals test)



Antistatic Footwear



Heel Energy Absorption



Hydrocarbon Resistance

↪ TECHNOLOGIES AND MATERIALS



No metal



ESD - Electrostatic Discharge



Metal-Free



High Visibility



Mondo Point 11



Extreme Lightness



Slip Resistance (optional glycerin test)



Slip Resistance on Inclined Roofs

↪ ANTI-SLIP RESULTS

*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	Forward heel (heel slip 7°) ≥ 0.31 ≥ 0.56	Backward heel (heel slip 7°) ≥ 0.36 ≥ 0.45	Ceramic tile floor with glycerin	Forward heel (heel slip 7°) ≥ 0.19 ≥ 0.35	Backward heel (heel slip 7°) ≥ 0.22 ≥ 0.35
SRA Ceramic + Nails	Flat ≥ 0.32 ≥ 0.39	Heel ≥ 0.28 ≥ 0.37	SRB Steel + Glicerol	Flat ≥ 0.18 ≥ 0.30	Heel ≥ 0.13 ≥ 0.20

↪ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slippiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

