

STRAUSS S3

TO880BP

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, back WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE antiperforation steel according to EN 12568

SOLE STABILE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4000 removable, anatomic, absorbing, antistatic and perspiring

Size 39-47 Shoe weight Sz 42 gr. 630



MATERIALS



TECHNOLOGIES



SECTORS



SOLE



Stabile is the comfortable alternative to the classic and "heavy" shoe for building sector.

This sole is highly performing with specific dowels, with dimensions and shapes to assure the maximum **stability**, with self-cleaning drainage channels to assure a perfect cleaning and with a

soft compound to isolate the foot to the continuous **shocks**. Line studied with a lot of attention to the technology of uppers and lightness of the materials.

ANTISLIPPING TEST RESULTS



SRA ceramic + NaLS	HEEL >= 0,28 FLAT >= 0,32	0,42 0,44
SRB steel + glycerol	HEEL >= 0,13 FLAT >= 0,18	0,20 0,18