

OXFORD S3

KU068D

CE UNI EN ISO 20345:2012 S3 SRC

High safety shoe, back WRU leather thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoes with refracting fabric insert.
Soft, lined and padded tongue.

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015 TOECAP 200J** polymeric **composite non-thermic** according to EN 12568
MIDSOLE flexible antiperforation composite fabric according to EN 12568
SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,
to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC INSOLE 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

Size 35-49 Shoe weight Sz 42 gr. 550



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
ANTISLIPPING TEST			
SRX	HEEL=0.620	0.40	
CONTRAC +	PLATEFORM=0.620	0.40	
SRB	HEEL=0.620	0.30	
SHOE +	PLATEFORM=0.620	0.30	