





BASKET S3

KU037N

CE UNI EN ISO 20345:2012 S3 SRC ESD

High safety shoe, Nubuck IDROTECH® WRU grain leather thickness

Perspiring and resistant to abrasion fabric lining.

Shoe with refracting fabric insert.

Soft, lined and padded tonque.

COMPLETELY METAL FREE SHOE

The shoe satisfies the requirements of slipping resistance on inclined roofs according to UNI 11583:2015

TOECAP 200J polymeric composite non-thermic according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping SRC INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial The shoe satisfies the requirement according to the norm IEC

61340-4-3:2001 for the electrical resistance

FSD

Size 36-47 Shoe weight Sz 42 gr. 570



CERTIFICATIONS











TECHNOLOGIES AND MATERIALS













SECTORS



COMPONENTS AND AUTOMOTIVE



WOOD METAL CARPENTRY



BUILDING AND HEAVY INDUSTRY



LOGISTICS AND LIGHT INDUSTRY



AREAS ROOFER **

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS



IDROTECH®

 $\ensuremath{\mathsf{IDROTECH}}\xspace\ensuremath{\mathbb{R}}$ is a leather treatment with the aim to optimize the water resistance and the foot perspiration. This particular tunning method, thanks to the used mineral salts, gives an excellent softness and a complete mechanical resistance to oils and hydrocarbons. The IDROTECH & leather is certified according to the norms ISO 4045, ISO 17075 and ISO 5403.

ANTISLIPPING TEST RESULTS

