

Ref. **9SHU150**

Multipurpose

High

High shoes



**HRO**



The +

- \*Lightness.
- \*Water-repellent.
- \*Comfort of use (insole HI-POLY foam + midsole EVA).
- \*Urban style.

### PURCHASE PACKAGING

Ref.	Size	Carton
9SHU150037	37	6
9SHU150038	38	6
9SHU150039	39	6
9SHU150040	40	6
9SHU150041	41	6
9SHU150042	42	6
9SHU150043	43	6
9SHU150044	44	6
9SHU150045	45	6
9SHU150046	46	6
9SHU150047	47	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

Trendy and timeless, SHUNGITE is a light and comfortable ESD shoe. Metal-free, SHUNGITE offers the wearer lightness, flexibility and resistance in wet conditions thanks to its water-repellent nubuck upper. The emphasis is on comfort: composite toe cap, textile anti-perforation midsole and Hi-Poly foam insole with cushions. The nitrile rubber outsole, non-slip on metal and steel floors, is also resistant to hydrocarbons and heat.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Anthracite	Closing	Lacing closure
Weight	555 g	Lining	Breathable 3D mesh
Upper	Water-repellent / Nubuck leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		
Insole	HI-POLY foam		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB20013172

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)