

Ref. **9SODH50**

Multipurpose

High

High shoes



S1P



0% METAL

The +

- * Breathable upper and lining.
- * Footbridge supplying torsional rigidity.
- * Midsole with front protective covering.

PURCHASE PACKAGING

Ref.	Size	Carton
9SODH50038	38	6
9SODH50039	39	6
9SODH50040	40	6
9SODH50041	41	6
9SODH50042	42	6
9SODH50043	43	6
9SODH50044	44	6
9SODH50045	45	6
9SODH50046	46	6
9SODH50047	47	6

Some sizes may only be available in certain countries



DESCRIPTION

Composite toecap
 Antipenetration textile sole
 External sole in double density PU/PU
 Upper in Suede
 Non woven lining
 Padded bellows
 Padded collar

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

TECHNICAL FEATURES

Color	Grey	Insole	Textile and foam, removable
Color 2	Blue	Main assembly	Injected
Weight	638 g	Closing	Lacing closure
Upper	Suede leather / Mesh	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/10/21/1787

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol