

Ref. **9PROH10**

Multipurpose

High

High shoes



### The +

- \*Soft PU/PU outsole: cushioning and comfort.
- \*Raised heel: stability on ladders.
- \*Wide cleats and flex lines: optimized adaptability to the ground.
- \*Nubuck upper with membrane: waterproof shoe.

### PURCHASE PACKAGING

Ref.	Size	Carton
9PROH10035	35	6
9PROH10036	36	6
9PROH10037	37	6
9PROH10038	38	6
9PROH10039	39	6
9PROH10040	40	6
9PROH10041	41	6
9PROH10042	42	6
9PROH10043	43	6
9PROH10044	44	6
9PROH10045	45	6
9PROH10046	46	6
9PROH10047	47	6
9PROH10048	48	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

CLAW PROOF is a lightweight, flexible and waterproof safety sneaker. With a membrane nubuck upper, CLAW PROOF ensures that the wearer's feet stay dry in wet weather.

Its low density PU/PU outsole guarantees all day comfort.

Its aluminum / composite protection system contributes to its sporty look.

### SECTORS

Light Industries

Regional/public authorities

Maintenance

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Reinforce-ment location	Front
Weight	683 g	Lining	Breathable 3D mesh
Upper	Nubuck leather	Defined heel	
Toecap	Aluminium		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	PU Foam, removable		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The tim einfluences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/10/24/2543 EXT 01/10/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S7S

Safety shoes

**S7S** Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance: - Sole puncture resistance (1100 Newton) - Non-metallic insert, 3.0mm diameter puncture needle-resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole - non-metallic insert type PS+ Water resistance of the entire shoe

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance

MAJ 10/12/2024