

Ref. **90KEC**

Specialties

Low

Sandals



### The +

- \*Easy-on and easy-off.
- \*Lightweight for use all day long.
- \*Semi-closed heel for extra stability.
- \*Antistatic outsole (A).
- \*Energy absorbing heel (E).

### PURCHASE PACKAGING

Ref.	Size	Carton
90KEC35	35	10
90KEC36	36	10
90KEC37	37	10
90KEC38	38	10
90KEC39	39	10
90KEC40	40	10
90KEC41	41	10
90KEC42	42	10
90KEC43	43	10
90KEC44	44	10
90KEC45	45	10
90KEC46	46	10
90KEC47	47	10

*Some sizes may only be available in certain countries*

See also

### VARIANTS



90KEH



90KEL

### DESCRIPTION

Composite toecap  
External sole in double density PU/PU  
Upper: breathable Microfiber in PU  
Breathable mesh lining

### SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

## TECHNICAL FEATURES

Color	White	Main assembly	Injected
Color 2	Grey	Closing	Back scratch strap
Weight	409 g	Lining	Breathable 3D mesh
Upper	Microfiber		
Toecap	Composite		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100374125**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

SB

Safety shoes

SB Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)