

Ref. MO4715

### Thermal Protection



### Heat Resistance



### The +

Long cuff for better protection  
Thermal contact insulation 250°C / 15 sec.  
Comfortable terry cotton

### PURCHASE PACKAGING

Réf.	Taille	Sachet	Carton
4715	10	5	60

### SALES PACKAGING

>1

Multiple

### DESCRIPTION

100% terry cotton support 850g/m<sup>2</sup> ; with protective long cuff 15cm in tough fabric.

### SECTORS

- Heavy & process industries
- Mechanicals constructions
- Light Industries
- Maintenance

### APPLICATIONS

General and heavy handling of hot objects: exiting furnaces, injection moulding machines, glass industry, metal working.

## TECHNICAL FEATURES

<b>Color</b>	Ecru
<b>Shape</b>	Glove
<b>Environment</b>	High heat
<b>Glove type</b>	Cut and sewn
<b>Support material</b>	100% terry cotton (850 g/m <sup>2</sup> )
<b>Glove construction</b>	Master
<b>Palm material</b>	Cotton
<b>Palm material type</b>	Cotton terry liner
<b>Back material</b>	Cotton
<b>Back material type</b>	Cotton terry liner
<b>Type Of Cuff</b>	Safety cuff / Straight cut
<b>Length - mm</b>	300

## STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate **0321/10428-01/E06000**

Delivered by SATRA Technology Centre Ltd (0321) Wyndham Way Telford Way Kettering- Northamptonshire- NN16 8SD United Kingdom



EN420:2003 + A1:2009

EN388:2016



2.2.3.1.X.

EN407:2004



X.2.X.X.X.X

EPI CAT. II

General requirements for protective gloves

Protection from mechanical risks

Protection from heat and fire

RETAILER STAMP