

Cut - Precision Work



DESCRIPTION

CLAW CUT range is a new generation of cut-resistant gloves, created to protect you in the most demanding tasks with a high level of cut resistance (from CUT D to A9) and offer excellent comfort and exceptional dexterity in all working environments (dry, wet and oily).

The CLAW CUT A9 400 is real revolution in cut protection with the highest level of cut resistance in the world (CUT A9, according to standard ANSI).

This glove was designed for precision work in dry and slightly oily environments.

The high gauge 18 together with an exceptionally soft and strong fiber (based on HPPE, recycled polyester, steel and spandex), give an exceptional comfort while providing an extraordinary performance.

The sandy nitrile coating and long reinforcement between thumb and forefinger give excellent grip. This coating provides excellent breathability (tested under COVERPERF label).

CLAW CUT A9 400 is made from recycled polyester and is RCS-certified (16% of total product weight).

This glove is touchscreen, so you can keep it on while using the touchscreen equipment.

Sanitized treatment: prevents the development of bacteria and odors, and CLAW CUT A9 400 is also hypoallergenic (COVERPERF SKINCARE test).

Dry Environment



The +

CUT A9: Highest level of cut protection in the world (standard ANSI)

COVERPERF BREATHABILITY: Maximum breathability for optimal comfort

COVERPERF DURABILITY: WASHABILITY (performance guaranteed for up to 5 cycles at 30°) for maximum durability

COVERPERF SKINCARE: Hypoallergenic to prevent irritation

Knit Knit Gauge 18: Comfort and exceptional dexterity

Nitrile sandy palm coating: Excellent grip in dry and slightly oily environment

Long crotch between thumb and index: Improved grip and tear prevention for maximum durability

RCS: Use of recycled materials (16%) to reduce environmental impact

HOT 1: Contact heat protection hot parts 100°C / 15 sec

Touchscreen, Sanitized

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1CL9400006	6	10	100
1CL9400007	7	10	100
1CL9400008	8	10	100
1CL9400009	9	10	100
1CL9400010	10	10	100
1CL9400011	11	10	100
1CL9400012	12	10	100

SALES PACKAGING

TECHNICAL FEATURES



Gauge 18

Color	Black
Glove type	Seamless knitting
Coating level	Palm
Material of coating	Nitrile
Coating finition	Sandy
Reinforced part place	Between thumb and index finger
Reinforced part material	Nitrile
Type Of Cuff	Elastic wrist

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0598/PPE/25/3877 Issue 1

Delivered by SGS Fimko Oy (0598) Takomotie 8 00380 HELSINKI Finland



EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN ISO 21420:2020

EN388:2016

+ A1:2018



4.X.4.3.F.

Protection from mechanical risks

ANSI



Cut resistance ANSI/SEA 105-2016 / ASTM F2992M-15

EN407:2020



X.1.X.X.X

Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)

COVERPERF - Breathability



Gloves tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 60mg/cm2/8h

COVERPERF -
Durability/Washable

COVERPERF - Skincare



Dermatological safety approved after direct contact with the skin for 48 hours. No irritation was observed at the end of the test.

MAJ 21/10/2025