

# YORK S3

KU061D

CE UNI EN ISO 20345:2012 S3 SRC

Low safety shoe, back WRU leather thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.  
Shoe with refracting fabric insert.  
Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

**Size 35-49 Shoe weight Sz 42 gr. 550**



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS

COMPONENTS AND AUTOMOTIVE  
LOGISTICS AND LIGHT INDUSTRY

WOOD METAL CARPENTRY



## SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRA	HEEL=0,30	0,45	
PLAT=0,32	0,48		
SRB	HEEL=0,30	0,30	
PLAT=0,30	0,29		