

ERCOLANO S3 HI HRO

HR066D

CE UNI EN ISO 20345:2012 S3 HI HRO SRC

High safety shoe, WRU back leather with WRU anti-scratch back leather thickness 1,8-2,0 mm in the heel zone.
Perspiring and abrasion resistant fabric lining.
Soft leather tongue. Shoe with fast device and leather coverlaces stitched with fireproof thread.
Side strap closing.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE HARD ROCK ANTISTATIC bidensity polyurethane and antistatic **RUBBER**.

Sole resistant to hydrocarbons and to abrasion, anti-shock and anti-slip SRC

INSOLE 4001 Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial.

Electrical resistance: *the values found prove that this insole is ESD*

HI heat insulation of sole complex

HRO resistance to hot contact of the outsole

Size 39-47 Shoe weight Sz 42 gr. 700




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



Hard Rock Antistatic is a shoe born to face the most extreme working conditions thanks to its rubber outsole. It has been studied to assure the maximum resistance to the most difficult weather conditions (from -30°C to 300°C) and the maximum protection against external cutting bodies (ex. slippers, etc.). Also uppers have been studied to face the most difficult working situations and for this reason the materials comply with the most advanced heat-insulating and water-repellent technologies.

PLUS



ZERO ABRASION

The Zero Abrasion technology is an anti-scratch leather, finished with a polyurethane multi-layer, that assures a complete protection of the upper against usury and abrasion. Highly resistant to water and oils, this leather is suitable for people who like wearing always clean and nice shoes even after months of usage.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRA	H&L2 >= 0,28	0,48	
SRA	PLAT >= 0,32	0,44	
SRB	H&L2 >= 0,10	0,22	
SRB	PLAT >= 0,08	0,20	