

# GYM EVO S3L FO SR

3M037NG

CE EN ISO 20345:2022 S3L FO SR ESD

High safety shoe, MICRO-tech technical fabric thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Soft, lined and padded tongue.

**COMPLETELY METAL FREE SHOE**

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015**

**TOECAP 200J** polymeric composite **non-thermic** according to EN 12568

**PL MIDSOLE** flexible antiperforation composite fabric according to EN 22568

**SOLE 3MOVE** three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping

**ANTITORSION** insert in the sole to assure stability on uneven ground

**INSOLE MEMORY, three-materials extracomfort** insole with soft latex Memory no-stress in the heel zone and in the bending point, resistant to the body pressure.

Perspiring, removable, anatomic, absorbing, antistatic and antibacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance ESD

**FO** sole resistance to hydrocarbons

**SR** sole resistance against slipping

**Size 36-47 Shoe weight Sz 42 gr. 560**



**NEW**

## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



3Move is a revolutionary line: thanks to the curved design of its sole, it guarantees the right posture while walking for all the shoe lifelong. Another characteristic is the heel relief area that allows a perfect weight cushioning. These peculiarities permit an extreme naturalness in walking that, at the end of the day, ensures a huge saving of energy and fatigue. 3Move belongs to the 3D generation. This shoe has 3 different layers with different densities in order to increase Comfort, Anti-slipping and foot Stability. All this line is equipped with the antitorcion insert in order to ensure an additional support at every step.

## PLUS



### 3D TRIPLA DENSITA' INIETTATA

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.

## ANTI SLIPPING SOLE

### ANTISLIPPING TEST RESULTS



**SRC**  
ANTI-SLIPPING SOLE

request results

SRA ceramic+NaLS	HEEL >= 0,28	0,38
	FLAT >= 0,32	0,40
SRB steel+glycerine	HEEL >= 0,13	0,27
	FLAT >= 0,18	0,34