





TIGER S3

3M457N

CE UNI EN ISO 20345:2012 S3 SRC ESD

High safety shoe, MICRO-tech technical fabric thickness 1,8-2,0

Technical external fabric and reflective tape.

Highly perspiring and abrasion resistant fabric lining.

Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

The shoe satisfies the requirements of slipping resistance on inclined roofs according to UNI 11583:2015

TOECAP 200J polymeric composite non-thermic according to EN

MIDSOLE flexible antiperforation composite fabric according to FN 12568

SOLE 3MOVE three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping SRC

ANTITORSION insert in the sole to assure stability on uneven around

INSOLE MEMORY, three-materials extracomfort insole with soft latex Memory no-stress in the heel zone and in the bending point, resistant to the body pressure.

Perspiring, removable, anatomic, absorbing, antistatic and antibacterial.

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 36-47 Shoe weight Sz 42 gr. 555



CERTIFICATIONS











TECHNOLOGIES AND MATERIALS

















SECTORS



COMPONENTS AND AUTOMOTIVE

WOOD METAL CARPENTRY

BUILDING AND HEAVY INDUSTRY

LOGISTICS AND LIGHT INDUSTRY

ROOFER ROOFER ARFAS

SOLE



3Move is a revolutionary line: thanks to the curved design of its sole, it guarantees the right posture while walking for all the shoe lifelong. Another characteristic is the heel relief area that allows a perfect weight cushioning. These peculiarities permit an extreme naturalness in walking that, at the end of the day, ensures a huge saving of energy and fatigue. 3Move belongs to the 3D generation. This shoe has 3 different layers with different densities in order to increase Comfort, Antislipping and foot Stability. All this line is equipped with the antitorsion insert in order to ensure an additional support at

ANTI SLIPPING SOLE

ANTISLIPPING TEST RESULTS



	request	results
SRA	HEEL >= 0,28	0,38
ceramic+NaLS	FLAT >= 0,32	0,40
SRB	HEEL >= 0,13	0,27
teel+glycerine	FLAT >= 0,18	0,34

PLUS



ANTI TORSION

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the centrla part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.



3D TRIPLA DENSITA' INIETTATA

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.