

# VERDI S3 R

AC880BRP

CE UNI EN ISO 20345:2012 S3 SRC

High safety shoe, water-resistant WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Lined and padded tongue. Shoe with fast device.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE antiperforation steel** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

**Size 39-47 Shoe weight Sz 42 gr. 560**




## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## PLUS

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
<b>SRC</b>			
SRA	HEEL >= 0,28	0,39	
PLATE	PLATE >= 0,28	0,39	
SMB	HEEL >= 0,23	0,39	
PLATE	PLATE >= 0,23	0,39	