

VERDI S3

AC880BP

CE UNI EN ISO 20345:2012 S3 SRC

High safety shoe, water-resistant WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE antiperforation steel according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

Size 36-49 Shoe weight Sz 42 gr. 550




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
SRC			
SRA	HEEL >= 0,28	0,39	
PLATE	PLATE >= 0,28	0,39	
SMB	HEEL >= 0,23	0,39	
PLATE	PLATE >= 0,23	0,39	