







WELDER S3L FO CI HI HRO SC SR

HR122D

CE EN ISO 20345:2022 S3L FO CI HI HRO SC SR

Low safety shoe, WPA back leather thickness 1,8-2,0 mm, with refracting fabric insert

Perspiring and abrasion resistant fabric lining.

Leather coverlaces stitched with fireproof thread.

Strap closing.

COMPLETELY METAL FREE SHOE

Toecap 200J polymeric composite non-thermic according to EN

MIDSOLE PL flexible antiperforation composite fabric according to EN 22568

HARD ROCK ANTISTATIC SOLE bidensity polyurethane and antistatic RUBBER.

Sole resistant to hydrocarbons and to abrasion, anti-shock and anti-

INSOLE 5000 trimaterial, extracomfort, perspiring, removable, anatomic, absorbing, ESD and antibacterial

FO sole resistance to hydrocarbons

CI cold insulation of sole complex -17°C

HI heat insulation of sole complex

HRO outsole resistance to hot contact

SC abrasion resistance of scuff cap

Size 39-47 Shoe weight size 42 gr. 590





CERTIFICATIONS















TECHNOLOGIES AND MATERIALS













SECTORS

WOOD METAL CARPENTRY

BUILDING AND HEAVY INDUSTRY



📥 OIL AND



₩ELDER

SOLE



Hard Rock Antistatic is a shoe born to face the most extreme working conditions thanks to its rubber outsole. It has been studied to assure the maximum resistance to the most difficult weather conditions (from -30°C to 300°C) and the maximum protection against external cutting bodies (ex. slipperies, etc.). Also uppers have been studied to face the most difficult working situations and for this reason the materials comply with the most advanced heat-insulating and water-repellent technologies.

ANTISLIPPING TEST RESULTS



PLUS